



DATA SHEET — FINAL VERSION

Resilient. Fast. Efficient.

Exos[®] CORVAULT Self Healing Storage



Exos[®] CORVAULT Self Healing Storage redefines petabyte-scale storage infrastructure with industry-leading innovation in every aspect of the system.



Product Highlights

- Effortlessly expand capacity with up to 2.120 PB raw (using 20 TB drives) in a maximum-density enclosure.
- Accelerate data access with performance up to 14 GB/s sequential read, 12 GB/s sequential write and 17,680 IOPS.
- Specially-tuned modular chassis maximises drive performance and longevity by protecting against vibrational and acoustic interference, heat and power irregularities.
- Engineered and manufactured by Seagate for tightly-integrated, highly-compatible and predictable performance.
- Capacity, reliability and speed - perfect for any macro-edge or core data centre.

Key Advantages

Introducing a new category of intelligent storage. Exos CORVAULT delivers sophisticated data protection, security and streamlined management to tackle the challenges of an exascale world.

Reliable and Self-healing. Field-proven design with five-nines (99.999%) availability. Autonomous Drive Regeneration (ADR) reduces human intervention and e-waste by automatically renewing hard drives "in situ" and on the fly.

Hyperscale-class efficiencies. Combining maximum data density of up to 2.120 PB raw (using 20 TB drives) in 4U with the latest hard drive technology delivers storage efficiencies similar to cutting-edge cloud service providers.

Architected for speed and resilience. Redundant active-active controllers powered by the 6th gen VelosCT ASIC and ADAPT erasure code data protection software dramatically streamline overhead, throughput, management and recovery.

Powerful configuration and management. One-button configuration accelerates deployment, while informative remote diagnostics and non-disruptive system updates simplify maintenance.

Seagate Secure built in. Hard drives are self-encrypting (SED) for maximum security without controller-level overhead. SFTP for secure file transfer. Optional FIPS 140-3 configuration.



Specifications	
Controllers	Redundant, active-active, hot-swappable controllers powered by gen 6 VelosCT ASIC
System Performance	14 GB/s sequential read throughput, 12 GB/s sequential write throughput, 17,680 IOPS
Device Support	Up to 106 Exos [®] self-encrypting SAS HDDs
Data Protection	Seagate ADAPT erasure coding -or- RAID 5, 6
Self healing technology	Autonomous Drive Regeneration (ADR)
Hot-Swappable Components	Eight removable expander cards, two per 24 HDD baseplane Redundant hot-swap drives, fans, power supplies
System Capacity	(1.908 PB raw) or (2.120 PB raw)
Physical	Height: 176.4 mm/6.94 in Width (excluding ears and rails): 441 mm/17.36 in Depth (including handles, excluding cables): 1139 mm/44.84 in Weight: 44.9 kg/99 lb Weight (with drives): 131.5 kg/290 lb
Host I/O Ports	Four mini-SAS HD ports, no expansion
Management	
Interface Types	10/100/1000 Ethernet
Protocols Supported	SNMP, SSL, SSH, SMTP, HTTP(S)
Management Consoles	Web-based GUI or Command Line Interface (CLI)
Management Software	Seagate Systems storage management console One-button configuration remote diagnostics non-disruptive updates
Power Requirements — AC Input	
Input Power Requirements	200V-240V AC, 50 Hz - 60 Hz
Max Power Output per PSU	2000W
Environmental/Temperature Ranges	
Operating/Non-operating Temperature	5°C to 35°C (41°F to 95°F, derated by 1°C per 300m above 900m) / -40°C to +70°C (-40°F to +158°F) (max rate of change: 20°C)
Operating/Non-operating Humidity	-12°C DP/10 to 80% (max) (non-condensing) / -12°C DP/5 to 100% (max) (non-condensing)
Operating/Non-operating Shock	3.0 g, 11 ms (per axis)/20.0 g, 7 ms, 10 shock pulses (2 shocks per axis X, Y in positive and negative direction, and 2 shocks in positive Z axis) OR ISTA 3H (mounted in a rack, horizontal impact on all sides, 4-in drop tests)
Operating/Non-operating Vibration	0.18 Grms, 5 Hz to 500 Hz, 30 min per axis / 0.54 Grms 6 Hz to 200 Hz (ISTA 3E)
Standards/Approvals	
Safety Certifications	UL 60950-1 (United States) CAN/CSA-C22.2 No.60950-1-07 (Canada) EN 60950-1 (European Union) IEC 60950-1 (International) CCC (China PRC – CCC Power Supplies) BIS (India – BIS Power Supplies)
Ecodesign	Commission Regulation (EU) 2019/424 (Directive 2009/125/EC)
Emissions (EMC)	FCC CFR 47 Part 15 Subpart B Class A (USA) ICES/NMB-003 Class A (Canada) EN 55032:2012 Class A (EU) AS/NZS CISPR 22/CISPR 32 Class A (Australia/New Zealand) VCCI Class A (Japan) KN 22/KN 32 Class A (S. Korea) CNS 13438 Class A (Taiwan)
Harmonics	EN 61000-3-2 (EU)
Flicker	EN 61000-3-3 (EU)
Immunity	EN 55024 (EU) KN 24/KN 35 (S. Korea)
Environmental Standards	The RoHS Directive (2011/65/EU) The WEEE Directive (2012/19/EU) The REACH Directive (EC) No. 1907/2006
Standard Marks/Approvals	United States, Canada, European Union (EU), Australia/New Zealand, Japan, China (PRC), Russia, Mexico, Germany, South Korea, Taiwan, India